

The effect of HIP treatment on mechanical properties of titanium aluminide additively manufactured by EBM

Friday, 8 December 2017 09:40 (25 minutes)

Titanium aluminide, one of important next generation high temperature materials, attracts intense R&D interests, and the application for aeronautics and space fields is seriously studied. TiAl components additively manufactured by us possesses more than 99% density and good mechanical properties, however residual voids are problematic in the area where cyclic properties are important, therefore HIP treatment is necessary. In this study, the effect of HIP treatment on the lamellar structure of TiAl alloy which showed excellent tensile ductility is investigated.

Please choose topic

HIP Process

Primary author: Mr KONDO, Daisuke (Technical Division Metal Technology Co.Ltd)

Co-authors: Dr IKEDA, Ayako (High-Performance Alloys Group High Temperature Materials Unit national Institute for Materials Science); Prof. YASUDA, Hiroyuki (Biomaterials & Structural Materials Design Area Course of Materials Science & Engineering Division of Materials & Manufacturing Science Graduate School of Engineering, Osaka University); Dr CHO, Ken (Biomaterials & Structural Materials Design Area Course of Materials Science & Engineering Division of Materials & Manufacturing Science Graduate School of Engineering, Osaka University); Mr UEDA, Minoru (Technical Division Metal Technology Co.Ltd.); Prof. NAKANO, Takayoshi (Biomaterials & Structural Materials Design Area Course of Materials Science & Engineering Division of Materials & Manufacturing Science Graduate School of Engineering, Osaka University); Mr NAGAMACHI, Yuto (Technical Division Metal Technology Co.Ltd.)

Presenter: JOSEPH, Robert (Metal Technology Co. Ltd.)

Session Classification: Materials

Track Classification: Materials